


Combo CAT6 KVM Switch


Optimize rack space. Maximize rack monitoring



Rear of KCC-108E



Rear of KCC-116E



Rear of KCC-132E



CAT6 KVM Dongle-USB&VGA (DGU)



VGA changer




HDMI changer



DP changer

Optional Remote IP Access

- An expansion slot allows you to add an optional KVM over IP module to enable remote access to your servers.
- Gain BIOS level access to your servers for system maintenance, support or failure recovery via secure SSL authentication and encryption.



Features

- Capable of connecting 32, 16 or 8 servers in 1U.
- Support interface VGA-USB.
- Up to 40 meters between server to KVM switch.
- USB local console, optional remote IP console.
- Cascade up to 8 levels, support mixed CAT6 & DB15 Combo KVM switch.
- Mixed USB/SUN & MAC with multi-platform switch Capability.
- Auto scan for monitoring PCs, easy select via push button, Hot keys and OSD.
- Hot pluggable, no software or driver required.
- Easy and quick installation.

| Part No. | KCC-108E | KCC-116E | KCC-132E |
|------------------------------------|---|--------------------|--------------------|
| No. of Computers | 8 | 16 | 32 |
| Max. no. of Computers | 232 (Daisy Chain) | 240 (Daisy Chain) | 256 (Daisy Chain) |
| KVM port connector | RJ 45 | | |
| Local Console | 1x HD DB15 for VGA (up to 1920x1440 resolution) 2x USB Type A for KB / Mouse | | |
| Optional IP Remote Console | 1x RJ45 connector for 10/100M Ethernet (up to 1600x1200 resolution) 1x DB9 male connector for modem, Null modem and serial power control 1x mini USB 2.0 receptacle | | |
| Daisy Chain | 1x DB15 (Female), up to 8 levels | | |
| Hot keys | Scroll-Lock, Caps-Lock, Num-Lock, Alt-Ctrl-Win | | |
| Compatibility | Mix PCs, SUNs and MACs, support Win7/Vista/2003/XP, Linux, Unix | | |
| Power | 100-240V AC 50/60Hz external power adapter | | |
| Environment | Operation temp.: 0 to 50°C Storage temp.: -20 to 60°C Humidity : 10% - 90%, non-condensing | | |
| Physical Dimensions / Net Weights | 448mm (W) x 167mm (D) x 44mm (H) / 3kg | | |
| Packing Dimensions / Gross Weights | 560*120*250mm / 3.5kg | | |

| Option Relate Item | | | |
|--------------------|----------------------------|--------------|---------------------|
| DGU | CAT6 KVM Dongle-USB&VGA | DVI changer | DVI-to-VGA changer |
| DP changer | DisplayPort-to-VGA changer | HDMI changer | HDMI-to-VGA changer |
| DIP-101 | KVM over IP module | | |

SAIS - Sacasa Industries & Systèmes
8 rue André Marie Ampère
28500 Vernouillet - France
09 70 440 600 - (+ 33) 970 440 600
<https://clavier-ecran-rackable.fr>
contact@sacasa.info