

# Combo CAT6 LCD Console Drawers

Optimize rack space. Maximize rack monitoring



## Features

Our range of LCD console drawers provides a variety of features that simplify to access servers to making system monitoring, troubleshooting and software upgrades.

The self-locking rails when in the fully extended/open position and the ultra convenient auto lock release when the LCD panel is closed, make for simple and hassle free operation.


Available with 17" or 19" A-Grade LCD panels, Combo CAT6 8, 16 or 32 port integrated KVM switch & additional one USB local console.

Using CAT5 or CAT6 ethernet cable, support max. Computer distance up to 40 meters away.


- Support combo interface, VGA-USB & VGA-PS/2.
- Additional one USB Local console to add local KB/Mouse & VGA.
- Up to 40 meters between Servers to KVM.
- Durable 104-key keyboard and touch pad.
- Quick and simple installation.
- Self-locking and auto release rails for ultra convenience.
- Port selection via push buttons or On-Screen-Display (OSD).
- Dedicated daisy chain port to expand up to 256 servers.



Rear of KVM-1708/1908ASL-M2/ULC



Rear of KVM-1716/1916ASL-M2/ULC



Rear of KVM-1732/1932ASL-M2/ULC

Part No.	KVM-1708ASL-M2/ULC	KVM-1716ASL-M2/ULC	KVM-1732ASL-M2/ULC	KVM-1908ASL-M2/ULC	KVM-1916ASL-M2/ULC	KVM-1932ASL-M2/ULC
Direct no. of Computers	8	16	32	8	16	32
Maximum no. of Computers	232(Daisy Chain)	240(Daisy chain)	256(Daisy chain)	232(Daisy Chain)	240(Daisy chain)	256(Daisy chain)
LCD	Size	17"		19"		
	Backlight	LED		LED		
	Resolution	1280*1024		1280*1024		
	Max. color	16.7M		16.7M		
	Luminance	250cd/m2		250cd/m2		
	View Angel (H/V)	176 / 170		170 / 160		
Contrast Ratio	1000 : 1		1000 : 1			
Port Selection	Push Button, OSD or Hotkey					
USB Local console	Yes , USB x2 for KB/ Mouse , VGA x1					
Max. Computer Distance	40 meters ( Servers to KVM )					
KB/Mouse Emulation	USB & PS2					
Rack Depth	500mm to 1100mm ( rack cabinet front rails to rear rails )					
Power	100-240V AC 50/60Hz via IEC Type power cord					
Environment	Operation temp: 0 to 50°C Storage temp: -20 to 60°C Humidity: 10% - 90%, non-condensing Shock: 10G acceleration ( 11ms duration) Vibration: 17 to 500Hz 1G PTP					
Physical Dimensions / Net Weights	448x42x580mm (WxHxD) / 12.0KG			448x42x580mm (WxHxD) / 12.5KG		
Packing Dimensions / Gross weights	715x140x780mm (WxHxD) / 18.0KG			715x140x780mm (WxHxD) / 18.5KG		

### Accessory

1.8meter IEC Type Power Cord

### Option Relate Item

DGU	CAT6 KVM Dongle-USB&VGA	DGP	CAT6 KVM Dongle -PS/2&VGA
DGD	CAT6 KVM Dongle-USB&DVI		



**SAIS - SACASA INDUSTRIES ET SYSTEMES**  
**2 Route DE GASVILLE - ESPACE BOAT - BAT B**  
**28630 NOGENT LE PHAYE - FRANCE**  
**TEL + 33 9 54 16 23 53 - contact@sacasa.info**