

# USB HUB DB15 LCD Console Drawers

Optimize rack space. Maximize rack monitoring



↑ (USB Port for device access)



Our range of LCD console drawers provides a variety of features that simplify to access servers to making system monitoring, troubleshooting and software upgrades.


The self-locking rails when in the fully extended open position and the ultra convenient auto lock release when the LCD panel is closed, make for simple and hassle free operation.

Available with 17.3" A-Grade LCD panels, combo DB15 8 or 16 port integrated KVM switch & additional one USB local console.


Support USB HUB 2.0 and touch screen enable function.

## Features

- Support USB interface, VGA-USB.
- Front 1x USB, Rear 2x USB 2.0 Type A, Sharing USB peripheral Device for computer (ex, flash disk , hard driver, KB/Mouse ).
- Additional one USB Local console to add local KB/Mouse & VGA.
- Durable 104-key keyboard and touch pad.
- Quick and simple installation.
- Self-locking and auto release rails for ultra convenience.
- Port selection via push buttons or On-Screen-Display (OSD).



Rear of KVM-1708WP-M2/ULC



Rear of KVM-1716WP-M2/ULC

Part No.		KVM-1708WP-M2/ULC		KVM-1716WP-M2/ULC	
Direct no. of Computers		8		16	
Maximum no. of Computers		8		16	
LCD	Size	17.3"			
	Backlight	LED			
	Resolution	1920*1080 Full HD ( support resolution up to 1920x1200 )			
	Max. color	262K			
	Luminance	300cd/m2			
	View Angel (H/V)	140 / 120			
Contrast Ratio		3000 : 1			
Port Selection		N/A	Push Button, OSD or Hotkey	N/A	Push Button, OSD or Hotkey
USB Local console		N/A	Yes, USB x2 for KB/ Mouse , VGA x1	N/A	Yes, USB x2 for KB/ Mouse , VGA x1
USB HUB		Yes, Front 1x USB 2.0 , Rear 2x USB 2.0 Type A for USB Peripheral Device			
Touch Screen		Yes, for option ( Driver needed )			
KB/Mouse Emulation		USB			
Rack Depth		500mm to 1100mm ( rack cabinet front rails to rear rails )			
Power		100-240V AC 50/60Hz via IEC Type power cord			
Environment		Operation temp: 0 to 50°C Storage temp: -20 to 60°C Humidity: 10% - 90%, non-condensing Shock: 10G acceleration ( 11ms duration) Vibration: 17 to 500Hz 1G PTP			
Physical Dimensions / Net Weights		448x42x600mm (WxHxD) / 12.5KG		448x42x600mm (WxHxD) / 13.0KG	
Packing Dimensions / Gross weights		720x190x800mm (WxHxD) / 18.5KG		720x190x800mm (WxHxD) / 19.5KG	
<b>Accessory</b>					
1.8meter IEC Type Power Cord (1.8meter VGA Cable Male to Male + 1.8meter USB Cable A Type to A Type for KVM-1701WP-M2)					
<b>Option Relate Item</b>					
CVU-018	1.8meter 2-in-1 KVM Cable-USB&VGA		CVU-030	3.0meter 2-in-1 KVM Cable-USB&VGA	
CVU-050	5.0meter 2-in-1 KVM Cable-USB&VGA				

**SAIS - Sacasa Industries & Systèmes**

**8 rue André Marie Ampère**

**28500 Vernouillet - France**

**09 70 440 600 - (+ 33) 970 440 600**

**<https://clavier-ecran-rackable.fr>**

**[contact@sacasa.info](mailto:contact@sacasa.info)**