



Combo DB15 LCD Console Drawers

Optimize rack space. Maximize rack monitoring
Waterproof Version



Our range of LCD console drawers provides a variety of features that simplify to access servers to making system monitoring, troubleshooting and software upgrades.

The self-locking rails when in the fully extended open position and the ultra-convenient auto lock release when the LCD panel is closed, make for simple and hassle free operation.

Available with 17" A-Grade LCD panels, combo DB15 single, 8 or 16 port integrated KVM switch.

LCD module front face compliant with IP65 waterproof grade, keyboard and touch pad module IP68 grade for tough environment application.

Features


- Support combo interface, VGA-USB & VGA-PS2. (single port VGA-USB)
- Short depth design suit for mobile rack and limited space.
- LCD front face IP65 waterproof grade.
- Silicon 98-key keyboard and touch pad IP68 waterproof grade.
- Quick and simple installation.
- Self-locking and auto release rails for ultra-convenience.
- Port selection via push buttons or On-Screen-Display (OSD).
- Dedicated daisy chain port to expand up to 240 servers.



Rear of KVM-1701S-AST-M2-IP



Rear of KVM-1708S-AST-M2-IP



Rear of KVM-1716S-AST-M2-IP

| Part No. | | KVM-1701S-AST-M2-IP | KVM-1708S-AST-M2-IP | KVM-1716S-AST-M2-IP |
|--|-----------------------------------|--|------------------------------------|---------------------|
| Direct no. of Computers | | 1 | 8 | 16 |
| Maximum no. of Computers | | 1 | 232(Daisy Chain) | 240(Daisy chain) |
| LCD | Size | 17" | | |
| | Backlight | LED | | |
| | Resolution | 1280*1024 | | |
| | Max.color | 16.7M | | |
| | Luminance | 250cd/m2 | | |
| | View Angel (H/V) | 176 / 170 | | |
| Contrast Ratio | | 1000 : 1 | | |
| Port Selection | | N/A | Push Button, OSD or Hotkey | |
| USB Local console / Expansion Slot | | N/A | | |
| KB/Mouse Emulation | | USB | USB & PS2 | |
| Rack Depth | | 380mm to 620mm (rack cabinet front rails to rear rails) | | |
| Power | | 100-240V AC 50/60Hz via IEC Type power cord | | |
| Environment | | Operation temp: 0 to 50°C Storage temp: -20 to 60°C Humidity: 10% - 90%, non-condensing Shock: 10G acceleration (11ms duration) Vibration: 17 to 500Hz 1G PTP | | |
| Physical Dimensions / Net Weights | | 443x42x457.2mm (WxHxD) /14KG | | |
| Packing Dimensions / Gross weights | | 605x168x700mm (WxHxD) /17KG | | |
| Accessory | | | | |
| 1.8meter IEC Type Power Cord (1.8meter VGA & USB A Type Cable for KVM-1701S-AST-M2-IP) | | | | |
| Option Relate Item | | | | |
| CVU-018 | 1.8meter 2-in-1 KVM Cable-USB&VGA | CVP-018 | 1.8meter 3-in-1 KVM Cable-PS/2&VGA | |
| CVU-030 | 3.0meter 2-in-1 KVM Cable-USB&VGA | CVP-030 | 3.0meter 3-in-1 KVM Cable-PS/2&VGA | |
| CVU-050 | 5.0meter 2-in-1 KVM Cable-USB&VGA | CVP-050 | 5.0meter 3-in-1 KVM Cable-PS/2&VGA | |

Rear of KVM-1716S-AST-M2-IP



Rear of KVM-1708S-AST-M2-IP



Rear of KVM-1701S-AST-M2-IP

