



(USB Port for device access)



Our range of LCD console drawers provides a variety of features that simplify to access servers to making system monitoring, troubleshooting and software upgrades.

The self-locking rails when in the fully extended open position and the ultra convenient auto lock release when the LCD panel is closed, make for simple and hassle free operation.

Available with 17" or 19" A-Grade LCD panels, integrated 8 ports USB-DVI & Audio KVM switch.

Support USB HUB 2.0 and touch screen enable function. Flexible dual rail design, capable LCD screen and keyboard tray operated independently.



Rear of KVMD-1708PD-M6 / KVM-1908D-WPD-M6

## Features

- Support USB-DVI & Audio interface.
- Support digital DVI and analog VGA input signal
- Dual slide rail capable LCD screen and keyboard tray independent operate.
- Front 1x USB, Rear 2x USB 2.0 Type A, Sharing USB peripheral Device for computer (ex, flash disk, hard driver, KB/Mouse).
- Additional two USB console port to add local KB/Mouse.
- Build in 2x 2 watts stereo speakers.
- Durable 104-key keyboard and touch pad.
- Quick and simple installation.
- Self-locking and auto release rails for ultra convenience.
- Port selection via push buttons or hotkey.

Part No.	KVMD-1708PD-M6		KVMD-1908PD-M6	
Direct no. of Computers			8	
Maximum no. of Computers			8	
LCD	Size	17"		19"
	Backlight	LED		LED
	Resolution	1920*1080 FULL HD		1920*1080 FULL HD
	Max.color	16.7 M		16.7 M
	Luminance	250cd/m2		250cd/m2
	View Angel (H/V)	176 / 170		170 / 160
	Contrast Ratio	1000 : 1		1000 : 1
Port Selection	Push Button, Hotkey			
USB Local console	Yes , USB x2 for KB/ Mouse			
USB HUB	1x Front , 2xRear USB 2.0 Type A for Peripheral USB Device			
Touch Screen	Yes , for option ( Driver needed )			
KB/Mouse Emulation	USB			
Rack Depth	500mm to 1100mm ( rack cabinet front rails to rear rails )			
Power	100-240V AC 50/60Hz via IEC Type power cord			
Environment	Operation temp: 0 to 50°C Storage temp: -20 to 60°C Humidity: 10% - 90%, non-condensing Shock: 10G acceleration ( 11ms duration) Vibration: 17 to 500Hz 1G PTP			
Physical Dimensions / Net Weights	449.8x44.4x685mm (WxHxD) / 13.0KG		449.8x44.4x685mm (WxHxD) / 13.5KG	
Packing Dimensions / Gross weights	710x185x910mm (WxHxD) / 20.0KG		710x185x910mm (WxHxD) / 20.5KG	
<b>Accessory</b>				
1.8meter IEC Type Power Cord				
<b>Option Relate Item</b>				
CD-018	1.8meter DVI-D Cable	CU-018	1.8meter USB Cable	
CA-018	1.8meter Audio Cable			