

Dual Rail Combo CAT6 LCD Console Drawers

Optimize rack space. Maximize rack monitoring



Features

The Anno range of LCD console drawers provides a variety of features that simplify to access servers to making system monitoring, troubleshooting and software upgrades.


Flexible dual rail design, capable LCD screen and keyboard tray operated independently.

The self-locking rails when in the fully extended open position and the ultra-convenient auto lock release when the LCD panel is closed, make for simple and hassle free operation.

Available with 17" or 19" A-Grade LCD panels, Combo CAT6 8, 16 or 32 port integrated KVM switch & additional one USB local console.

Using CAT5 or CAT6 ethernet cable, support max. Computer distance up to 40 meters away.


- Support combo interface, VGA-USB & VGA-PS/2.
- Additional one USB Local console to add local KB/Mouse & VGA.
- Dual slide rail capable LCD screen and keyboard tray independent Operate.
- Up to 40 meters between Servers to KVM.
- Durable 104-key keyboard and touch pad.
- Quick and simple installation.
- Self-locking and auto release rails for ultra-convenience.
- Port selection via push buttons or On-Screen-Display (OSD).



Rear of KVMD-1708/1908ASL-M6/ULC



Rear of KVMD-1716/1916ASL-M6/ULC



Rear of KVMD-1732/1932ASL-M6/ULC

Part No.	KVMD-1708ASL-M6/ULC	KVMD-1716ASL-M6/ULC	KVMD-1732ASL-M6/ULC	KVMD-1908ASL-M6/ULC	KVMD-1916ASL-M6/ULC	KVMD-1932ASL-M6/ULC
Direct no. of Computers	8	16	32	8	16	32
Maximum no. of Computers	232(Daisy Chain)	240(Daisy chain)	256(Daisy chain)	232(Daisy Chain)	240(Daisy chain)	256(Daisy chain)
LCD	Size	17"		19"		
	Backlight	LED		LED		
	Resolution	1280*1024		1280*1024		
	Max.color	16.7M		16.7M		
	Luminance	250cd/m2		250cd/m2		
	View Angel (H/V)	176 / 170		170 / 160		
Contrast Ratio	1000 : 1		1000 : 1			
Port Selection	Push Button, OSD or Hotkey					
USB Local console	Yes, USB x2 for KB/ Mouse, VGA x1					
Max. Computer Distance	40 meters (Servers to KVM)					
KB/Mouse Emulation	USB & PS2					
Rack Depth	522mm to 1100mm (rack cabinet front rails to rear rails)					
Power	100-240V AC 50/60Hz via IEC Type power cord					
Environment	Operation temp: 0 to 50°C Storage temp: -20 to 60°C Humidity: 10% - 90%, non-condensing Shock: 10G acceleration (11ms duration) Vibration: 17 to 500Hz 1G PTP					
Physical Dimensions / Net Weights	449.8x44.4x685mm (WxHxD) / 13.0KG			449.8x44.4x685mm (WxHxD) / 13.5KG		
Packing Dimensions / Gross weights	710x185x910mm (WxHxD) / 20.0KG			710x185x910mm (WxHxD) / 20.5KG		

Accessory

1.8meter IEC Type Power Cord

Option Relate Item

DGU	CAT6 KVM Dongle-USB&VGA	DGP	CAT6 KVM Dongle -PS/2&VGA
DGD	CAT6 KVM Dongle-USB&DVI		



China (Factory)

Add : The south faces industry area of Xia Gang Fu Hai road, Chang'an Town, Dongguan City, Guangdong, China.

Tel : +86-769-81666360, 81666395-97

Fax : +86-769-81666306

Email : sales@annso.com.tw

Taiwan (Head Quarter)

Anno Technology Co., Ltd.

NO.53, Ming YI Street, Luzhou Dist. New Taipei City, Taiwan

Email : sales@annso.com.tw