

Rugged Military Grade 8/16 ports LCD KVM Switch

Optimize rack space. Maximize rack monitoring




Features

- Meet MIL-STD-810F/G standard
- 1U 17.3" LCD Console Drawer, support 1920x1080 resolution
- Support up to 1920 x 1200 resolution
- Bulid-in 8/16 port combo KVM switch, support VGA-USB & VGA-PS/2.
- Additional one USB Local console to add local KB/Mouse & VGA.
- Sealed 104-keys IP65 silicone keyboard and touchpad with backlight
- MIL connector for power input
- Self-locking and auto release rails for ultra convenience
- Port selection via push buttons or On-Screen-Display (OSD)


Options

- DC 9~36V power input
- High brightness LCD panel, up to 1000 nits
- Front AR or EMC glass protect screen

Rear of KVM-1708W-AST-M8/ULC



Rear of KVM-1716W-AST-M8/ULC



Part No.		KVM-1708W-AST-M8/ULC	KVM-1716W-AST-M8/ULC
Direct no. of Computers		8	16
KVM Connectors		232 (Daisy Chain)	240 (Daisy Chain)
LCD	Size	17.3"	
	Backlight	LED	
	Resolution	1920*1080 Full HD (support resolution up to 1920x1200)	
	Max.color	262K	
	Luminance	300cd/m2	
	View Angel (H/V)	140 / 120	
	Contrast Ratio	650 : 1	
Port Selection		Push Button, Hotkey	
USB Local console		Yes, USB x 2 for KB/Mouse, VGA x 1	
KB/Mouse Emulation		USB & PS2	
Rack Depth		600mm to 1000mm (rack cabinet front rails to rear rails)	
Power		100-240V AC 50/60Hz via 3 pins lock connector	
Environment (MIL-STD-810G)		Operation temp: 0 to 50°C	(MIL-STD-810, Method 501.5 & 502.5)
		Storage temp: -20 to 60°C	(MIL-STD-810, Method 501.5 & 502.5)
		Humidity: 10% - 90%, non-condensing	(MIL-STD-810, Method 507.5)
		Shock/Vibration: Procedure VI, 50G @ 11ms	(MIL-STD-810, Method 516.6)
		Altitude: 10,000 ft Operational, 30,000 ft Storage	(MIL-STD-810, Method 500.5)
Physical Dimensions / Net Weights		482x42x600mm (WxHxD) /13KG	
Packing Dimensions / Gross weights		720x160x860mm(WxHxD) /19KG	
Accessories			
1 x 1.8 Power Cord with lock connector			
Option Relate Item			
CVU-018	1.8meter 2-in-1 KVM Cable-USB&VGA	CVP-018	1.8meter 3-in-1 KVM Cable-PS/2&VGA
CVU-030	3.0meter 2-in-1 KVM Cable-USB&VGA	CVP-030	3.0meter 3-in-1 KVM Cable-PS/2&VGA
CVU-050	5.0meter 2-in-1 KVM Cable-USB&VGA	CVP-050	5.0meter 3-in-1 KVM Cable-PS/2&VGA

SAIS - Sacasa Industries & Systèmes

8 rue André Marie Ampère

28500 Vernouillet - France

09 70 440 600 - (+ 33) 970 440 600

<https://clavier-ecran-rackable.fr>

contact@sacasa.info