



Rugged Military Grade 8/16 ports LCD KVM Switch

Optimize rack space. Maximize rack monitoring



Rear of KVM-1708/1908AST-M8



Rear of KVM-1716/1916AST-M8

Features

- Meet MIL-STD-810F/G standard
- 1U 17" or 19" LCD Console Drawer, wide operation temperature support 1280 x 1024 resolution
- Bulid-in 8/16 port combo KVM switch, support VGA-USB & VGA-PS/2.
- Sealed 104-keys IP65 silicone keyboard and touchpad with backlight
- MIL connector for power input
- Self-locking and auto release rails for ultra convenience
- Port selection via push buttons or On-Screen-Display (OSD)

Options

- DC 9~36V power input
- High brightness LCD panel, up to 1000 nits
- Front AR or EMC glass protect screen

Optional Remote IP Access

- An expansion slot allows you to add an optional KVM over IP module to enable remote access to your servers.
- Gain BIOS level access to your servers for system maintenance, support or failure recovery via secure SSL authentication and encryption.



Part No.	KVM-1708AST-M8	KVM-1716AST-M8	KVM-1908AST-M8	KVM-1916AST-M8
Direct no. of Computers	8	16	8	16
KVM Connectors	232 (Daisy Chain)	240 (Daisy Chain)	232 (Daisy Chain)	240 (Daisy Chain)
LCD	Size	17"		19"
	Backlight	LED		LED
	Resolution	1280 x 1024		1280 x 1024
	Max.color	16.7M		16.7M
	Luminance	350cd/m2		450cd/m2
	View Angel (H/V)	170 / 160		170 / 160
Contrast Ratio	1000 : 1		1000 : 1	
Port Selection	Push Button, Hotkey			
Expansion Slot	Yes, option for Remote IP Access			
KB/Mouse Emulation	USB & PS2			
Rack Depth	600mm to 1000mm (rack cabinet front rails to rear rails)			
Power	100-240V AC 50/60Hz via 3 pins lock connector			
Environment (MIL-STD-810G)	Operation temp: -20 to 70°C		(MIL-STD-810, Method 501.5 & 502.5)	
	Storage temp: -30 to 80°C		(MIL-STD-810, Method 501.5 & 502.5)	
	Humidity: 5% - 95%, non-condensing		(MIL-STD-810, Method 507.5)	
	Shock/Vibration: Procedure VI, 50G @ 11ms		(MIL-STD-810, Method 516.6)	
	Altitude: 10,000 ft Operational, 30,000 ft Storage		(MIL-STD-810, Method 500.5)	
Physical Dimensions / Net Weights	482x42x600mm (WxHxD) /13KG			
Packing Dimensions / Gross weights	720x160x860mm(WxHxD) /19KG			
Accessories				
1 x 1.8 Power Cord with lock connector				
Option Relate Item				
CVU-018	1.8meter 2-in-1 KVM Cable-USB&VGA	CVP-018	1.8meter 3-in-1 KVM Cable-PS/2&VGA	
CVU-030	3.0meter 2-in-1 KVM Cable-USB&VGA	CVP-030	3.0meter 3-in-1 KVM Cable-PS/2&VGA	
CVU-050	5.0meter 2-in-1 KVM Cable-USB&VGA	CVP-050	5.0meter 3-in-1 KVM Cable-PS/2&VGA	

SAIS - Sacasa Industries & Systèmes
 8 rue André Marie Ampère
 28500 Vernouillet - France
 09 70 440 600 - (+ 33) 970 440 600
<https://clavier-ecran-rackable.fr>
contact@sacasa.info