



NOTE:
 1: MATERIAL:
 2: ALL BURRS MUST BE FILLETED (R5) MIN
 3: FINISH: COATING (SPEC. SEE SAMPLE COLOR PANTONE 413C
 4: TOLREANCE UNLESS OTHERWISE SPEC. SEE TOLERANCE TABLE

| | | | | | | |
|-----|------------|---------|-----------|-----------|-------------|----------------|
| TOL | < 30 | : ±0.1 | UNIT : mm | FINISHING | PART NO. | Ver. A |
| | 30 < 120 | : ±0.15 | | 3RD ANGLE | MOLD NO. | Q'ty |
| | 120 < 315 | : ±0.2 | | APPROVED | TITLE | RM-2X-6-4-ASSY |
| | 315 < | : ±0.3 | | CHECKED | DRAWING NO. | RM-2X-6-4-3D |
| | ANGLE TOL: | : ±0.5° | | DESIGNED | SCALE | 1:1 |
| | | | | DRAWN | SIZE A2 | SHEET 1 OF 1 |

SAIS - Sacasa Industries & Systèmes
 8 rue André Marie Ampère
 28500 Vernouillet - France
 09 70 440 600 - (+ 33) 970 440 600
<https://clavier-ecran-rackable.fr>
contact@sacasa.info

| MARK | DESCRIPTION | SING | DATE |
|------|-------------|------|------|
| △ | | | |
| △ | | | |
| △ | | | |