



Self-contained Portable Workstation Solution

The PWS670P-17W-T3 is a portable workstation, intergrated with 3 x 17.3" LCDs. It is designed to pack the highest desktop PC performance in a portable package. It comes in a road-ready lunchbox style portable enclosure constructed of aluminum alloy. Protective corner rubber bumpers help to absorb shock during transport, or in the field. It includes a spacious enclosure that supports up to E-ATX motherboard, 4 driver bays for data storage devices, and 7 expansion slots for add-on cards.

The keyboard folds out for use and includes a touchpad mouse. Space for standard PS2 size power supply. A rubber-clad carrying handle makes carrying the system easy, and a luggable carry case with wheels let you transport the system over long distances more easily.

Features

- Custom-build and expandable portable workstation
- Aluminum alloy construction
- Supports up to E-ATX form-factor desktop and server system boards and configurable with latest Intel multi-core processors
- Supports PCI, PCI-X and PCI-Express slots for add-on cards
- Integrated triple 17.3" active matrix flat panel display, support FHD 1080p resolution
- External 2 drive bays: 1 x 3.5" drive bays, 1 x slim-line drive bays for optical drive, internal 2 x 2.5" HDD bay
- Integrated keyboard with touchpad pointing device
- Space for standard PS2 size power supply

Model	PWS670P-17W-T3
Motherboard	Support up to E-ATX
Slots	Offer 7 expansion slots
Display	Triple 17.3" LCD Display, 1920x 1080, 300 nits ,262K colors, 650:1 contrast , tempered strengthen glass to protect screen
Drive bay	1 x 3.5", externally accessible driver bays 1 x slim-type optical driver bay 2 x 2.5" internally HDD bay
Video	AD conversion board, 3 x HDMI interface (Optional Display port)
KB/ MS	104-key industrial Keyboard/ touchpad
Power Supply	Space for standard PS2 size power supply
Construction	Rugged Aluminum Construction with rubber corner bumpers , tilt-up feet under chassis
Speaker	Built-in amplified 2x 2W speakers
Physical Dimensions/ Net Weights	463 x 372 x 265 mm (WxHxD) / 18 KG
Packing Dimensions/ Gross weights	660 x 580 x 430 (WxHxD) / 32.5KG
Carrying Case	Aluminum carrying case with wheels
Operating Temperature	0°C~50°C
Storage Temperature	-20°C~60°C
Relative Humidity	10%~95% (non-condensing)
Certificate	CE, FCC, RoHS

