

# Dual Rail DVI LCD Console Drawers

Optimize rack space. Maximize rack monitoring



(USB Port for device access)




Our range of LCD console drawers provides a variety of features that simplify to access servers to making system monitoring, troubleshooting and software upgrades.

The self-locking rails when in the fully extended open position and the ultra convenient auto lock release when the LCD panel is closed, make for simple and hassle free operation.

Available with 17" or 19" A-Grade LCD panels, integrated 12 ports USB-DVI & Audio KVM switch.

Support USB HUB 2.0 and touch screen enable function. Flexible dual rail design, capable LCD screen and keyboard tray operated independently.



## Features

- Support USB-DVI & Audio interface.
- Support digital DVI and analog VGA input signal
- Dual slide rail capable LCD screen and keyboard tray independent operate.
- Front 1x USB, Rear 2x USB 2.0 Type A, Sharing USB peripheral Device for computer (ex, flash disk, hard driver, KB/Mouse).
- Additional two USB console port to add local KB/Mouse.
- Build in 2x 2 watts stereo speakers.
- Durable 104-key keyboard and touch pad.
- Quick and simple installation.
- Self-locking and auto release rails for ultra convenience.
- Port selection via push buttons or hotkey.

Part No.		KVMD-1708PD-M6	KVMD-1908PD-M6
Direct no. of Computers		12	
Maximum no. of Computers		12	
LCD	Size	17"	19"
	Backlight	LED	LED
	Resolution	1280*1024	1280*1024
	Max.color	16.7 M	16.7 M
	Luminance	250cd/m2	250cd/m2
	View Angel (H/V)	176 / 170	170 / 160
	Contrast Ratio	1000 : 1	1000 : 1
Port Selection		Push Button, Hotkey	
USB Local console		Yes , USB x2 for KB/ Mouse	
USB HUB		1x Front , 2xRear USB 2.0 Type A for Peripheral USB Device	
Touch Screen		Yes , for option ( Driver needed )	
KB/Mouse Emulation		USB	
Rack Depth		500mm to 1100mm ( rack cabinet front rails to rear rails )	
Power		100-240V AC 50/60Hz via IEC Type power cord	
Environment		Operation temp: 0 to 50℃ Storage temp: -20 to 60℃ Humidity: 10% - 90%, non-condensing Shock: 10G acceleration ( 11ms duration) Vibration: 17 to 500Hz 1G PTP	
Physical Dimensions / Net Weights		449.8x44.4x685mm (WxHxD) / 13.0KG	449.8x44.4x685mm (WxHxD) / 13.5KG
Packing Dimensions / Gross weights		710x185x910mm (WxHxD) / 20.0KG	710x185x910mm (WxHxD) / 20.5KG
Accessory			
1.8meter IEC Type Power Cord			
Option Relate Item			
CD-018	1.8meter DVI-D Cable	CU-018	1.8meter USB Cable
CA-018	1.8meter Audio Cable		

**SAIS - Sacasa Industries & Systèmes**

**8 rue André Marie Ampère**

**28500 Vernouillet - France**

**09 70 440 600 - (+ 33) 970 440 600**

**<https://clavier-ecran-rackable.fr>**

**[contact@sacasa.info](mailto:contact@sacasa.info)**