



Rugged Military Grade Combo DB15 LCD KVM Switch

Optimize rack space. Maximize rack monitoring




Features


- Meet MIL-STD-810F/G standard
- 1U 17.3" LCD drawer
- Support 1920 x 1080 FHD resolution
- Short depth design suit for mobile rack and limited space
- Support combo interface, VGA-USB & VGA-PS/2
- Sealed IP65 silicone keyboard and trackball with backlight
- MIL connector for power input
- Self-locking and auto release rails for ultra convenience
- Port selection via push buttons or On-Screen-Display (OSD).
- Dedicated daisy chain port to expand up to 240 servers.

Options

- DC 9~36V power input
- High brightness LCD panel, up to 1000 nits
- Front AR or EMC glass protect screen



Rear of KVM-1708SW-AST-M8-Trackball



Rear of KVM-1716SW-AST-M8-Trackball

Part No.	KVM-1708SW-AST-M8-Trackball	KVM-1716SW-AST-M8-Trackball	
Direct no. of Computers	8	16	
Maximum no. of Computers	232(Daisy Chain)	240(Daisy chain)	
LCD	Size	17.3"	
	Backlight	LED	
	Resolution	1920*1080 Full HD (support resolution up to 1920x1200)	
	Max.color	262K	
	Luminance	300cd/m2	
	View Angel (H/V)	140 / 120	
	Contrast Ratio	650 : 1	
Port Selection	Push Button, Hotkey		
USB Local Console	N/A		
KB/Mouse Emulation	USB & PS2		
Rack Depth	450 mm to 650mm (rack cabinet front rails to rear rails)		
Power	100-240V AC 50/60Hz via 3 pins lock connector		
Environment (MIL-STD-810G)	Operation temp: 0 to 50°C	(MIL-STD-810, Method 501.5 & 502.5)	
	Storage temp: -20 to 60°C	(MIL-STD-810, Method 501.5 & 502.5)	
	Humidity: 10% - 90%, non-condensing	(MIL-STD-810, Method 507.5)	
	Shock/Vibration: Procedure VI, 50G @ 11ms	(MIL-STD-810, Method 514.6 & 516.6)	
	Altitude: 10,000 ft Operational, 30,000 ft Storage	(MIL-STD-810, Method 500.5)	
Physical Dimensions / Net Weights	482x43x460mm (WxHxD) /14KG		
Packing Dimensions / Gross weights	605x168x700mm (WxHxD) /17KG		
Accessories			
1 x 1.8 Power Cord with lock connector			
Option Relate Item			
CVU-018	1.8meter 2-in-1 KVM Cable-USB&VGA	CVP-018	1.8meter 3-in-1 KVM Cable-PS/2&VGA
CVU-030	3.0meter 2-in-1 KVM Cable-USB&VGA	CVP-030	3.0meter 3-in-1 KVM Cable-PS/2&VGA
CVU-050	5.0meter 2-in-1 KVM Cable-USB&VGA	CVP-050	5.0meter 3-in-1 KVM Cable-PS/2&VGA

SAIS - Sacasa Industries & Systèmes

8 rue André Marie Ampère

28500 Vernouillet - France

09 70 440 600 - (+ 33) 970 440 600

<https://clavier-ecran-rackable.fr>

contact@sacasa.info