

# Combo DB15 LCD Console Drawers

Optimize rack space. Maximize rack monitoring



The Anso range of LCD console drawers provides a variety of features that simplify to access servers to making system monitoring, troubleshooting and software upgrades.

The self-locking rails when in the fully extended/open position and the ultra convenient auto lock release when the LCD panel is closed, make for simple and hassle free operation.

Configure with 21.5 or 23.8 inch A-Grade FHD LCD panels, combo DB15 8 or 16 port integrated KVM switch & with an option remote IP console.


## Optional Remote IP Access

- An expansion slot allows you to add an optional KVM over IP module to enable remote access to your servers.
- Gain BIOS level access to your servers for system maintenance, support or failure recovery via secure SSL authentication and encryption.




## Features

- Support combo interface, GA-USB & VGA-PS/2.
- Durable 104-key keyboard and touch pad.
- Quick and simple installation.
- Self-locking and auto release rails for ultra convenience.
- Port selection via push buttons or On-Screen-Display (OSD).
- Dedicated daisy chain port to expand up to 240 servers.
- Access Control List (ACL) security function for up to 8 independent user accounts.



Rear of KVM-2108AST-M2  
Rear of KVM-2408AST-M2



Rear of KVM-2116AST-M2  
Rear of KVM-2416AST-M2

Part No.		KVM-2108AST-M2	KVM-2116AST-M2	KVM-2401AST-M2	KVM-2408AST-M2	KVM-2416AST-M2
Direct no. of Computers		8	16	1	8	16
Maximum no. of Computers		232(Daisy Chain)	240(Daisy chain)	1	232(Daisy Chain)	240(Daisy chain)
LCD	Size	21.5"		23.8"		
	Backlight	LED		LED		
	Resolution	1920*1080 FULL HD (up to 1920*1200)		1920*1080 FULL HD (up to 1920*1200)		
	Max.color	16.7M		16.7M		
	Luminance	250cd/m2		250cd/m2		
	View Angel (H/V)	178 / 178		178 / 178		
Contrast Ratio		3000 : 1		1000 : 1		
Port Selection		Push Button, OSD or Hotkey		N/A	Push Button, OSD or Hotkey	
Expansion Slot		Yes, option for Remote IP Access		N/A	Yes, option for Remote IP Access	
KB/Mouse Emulation		USB & PS2				
Rack Depth		500mm to 1100mm ( rack cabinet front rails to rear rails )				
Power		100-240V AC 50/60Hz via IEC Type power cord				
Environment		Operation temp: 0 to 50°C Storage temp: -20 to 60°C Humidity: 10% - 90%, non-condensing Shock: 10G acceleration ( 11ms duration) Vibration: 17 to 500Hz 1G PTP				
Physical Dimensions / Net Weights		448x42x775mm / 18.5 KG			448x42x775mm / 19.5 KGs	
Packing Dimensions / Gross weights		730x260x880mm / 24 KG			730x260x880mm / 25 KGs	

### Accessory

1.8meter IEC Type Power Cord (1.8meter VGA& PS2Cable + 1.8meter USB A Type Cable for KVM-1701/1901AST-M6 )

### Option Relate Item

CVU-018	1.8meter 2-in-1 KVM Cable-USB&VGA	CVP-018	1.8meter 3-in-1 KVM Cable-PS/2&VGA
CVU-030	3.0meter 2-in-1 KVM Cable-USB&VGA	CVP-030	3.0meter 3-in-1 KVM Cable-PS/2&VGA
CVU-050	5.0meter 2-in-1 KVM Cable-USB&VGA	CVP-050	5.0meter 3-in-1 KVM Cable-PS/2&VGA
DIP-101	KVM over IP module for Remote Bios Level Access		

**SAIS - Sacasa Industries & Systèmes**

8 rue André Marie Ampère

28500 Vernouillet - France

09 70 440 600 - (+ 33) 970 440 600

<https://clavier-ecran-rackable.fr>

[contact@sacasa.info](mailto:contact@sacasa.info)