

Rack Mount Industrial Display Drawer

Model #RMD-15UXGA



Features

- 1U Foldable Compact 19 inch rack mountable
- 15 inch 1600 x 1200 resolution
- DVI-D, VGA, Audio input
- Heavy duty steel chassis construction
- Front osd control buttons to optimized display
- Build in 2x 2watts stereo speakers
- Self-Locking and Auto Release rail for ultra convenience

Option

- Composite video input
- HDMI or Display port input
- 3G / HD / SD-SDI broadcast grade input
- DC 9~36 V power input
- AR Hardness glass



Rear of RMD-15UXGA

LCD Characteristics :

Screen Size	15"
Backlight Type	LED a-si TFT
Resolution	1600*1200
Contrast Ratio	1000:1
Brightness (cd/m2)	1000
View Angles (H/V)	160/140
Pixel Size (HxV) mm	0.1905x0.1905
Max. Color	262K
MTBF (Hrs.)	30,000

Input Signals:

DVI-D	DVI-D 24Pin Connector (Female)
VGA	D-SUB 15Pin Connector (Female)
Audio	3.5" Jack
Power Input	Standard IEC Inlet
Touch-USB (option)	USB A Type connector
Touch-RS232 (option)	D-SUB 9P connector (Female)

Power Specifications :

AC Power Input	Standard IEC Type Power Cord with Internal Power adapter, 100-240V AC Input
Wide Range DC Power Input (option)	Screw Type Terminal Block with internal wide Range DC 9-36V power module

User Controls Interface:

Power ON / OFF via Front Button
Power Mode Status LED indicator
OSD (On Screen Display) Buttons

Mechanical and Environment:

Height	1U Foldable
Rack Depth	15.5" to 30" (cabinet front rail to rear rail)
Mounting	Rack Mount with tilt adjustment
Construction	Metal Housing
Operating Temperature	-30- 70 deg. C
Operating Humidity	5% - 95% (non -condensing)
Anti-Vibration	10 - 55 Hz
Anti-Shock	15G / Peak (6 ms)
Physical Dimension (WxHxD)	448 x 44 x 425 (mm)
Packing Dimension (WxHxD)	610 x 170 x 700 (mm)
Net Weight / Gross Weight	12.5 / 17 (KGs)
Certification and Approvals	CE / FCC / RoHS

