(USB Port for device access)

HDMI LCD console drawers provide a variety of features that simplify to access servers to making system monitoring, troubleshooting and software upgrades.
The self-locking rails when in the fully extended open position and the ultra convenient auto lock release when the LCD panel is closed, make for simple and hassle-free operation.
Available with 17.3"4K A-Grade LCD panels, integrated 8 ports USB-HDMI KVM switch.

Rear of KVM-1708SWHD-M2-4K

## Features

- 17.3" 4K 3840 x 2160 resolution
- Support 1920 x 1080 & 1920 x 1200 resolution
- Support USB-HDMI interface.
- 8 ports HDMI 2.0 input
- Front 1x USB, Rear 1x USB 2.0 Type A, Sharing USB peripheral Device for computer (ex, flash disk, hard driver, KB/Mouse).
- Additional two USB console port to add local KB/Mouse.
- Build in 2x 2 watts stereo speakers.
- Durable 104-key keyboard and touch pad.
- Quick and simple installation.
- Self-locking and auto release rails for ultra convenience.
- Port selection via push buttons or hotkey.

Part No.	KVM-1708SWHD-M2-4K
Direct no. of Computers	8
Maximum no. of Computers	8

LCD	Size	17.3"
	Backlight	LED
	Resolution	4K resolution 3840 x 2160
	Max.color	16.7M
	Luminance	400cd/m2
	View Angel (H/V)	178 / 178
	Contrast Ratio	1000 : 1

Port Selection	Push Button, Hotkey
USB Local console	Yes , USB x2 for KB/ Mouse
USB HUB	1x Front , 1xRear USB 2.0 Type A for Peripheral USB Device
KB/Mouse Emulation	USB
Rack Depth	450mm to 650mm (rack cabinet front rails to rear rails)
Power	100-240V AC 50/60Hz via IEC Type power cord
Environment	Operation temp: 0 to 50℃ Storage temp: -20 to 60℃ Humidity: 10% - 90%, non-condensing Shock: 10G acceleration (11ms duration) Vibration: 17 to 500Hz 1G PTP
Physical Dimensions / Net Weights	443x42x457.2mm (WxHxD) /11KG
Packing Dimensions / Gross weights	710x190x620mm (WxHxD) / 16.5KG

Accessory	
1.8meter IEC Type Power Cord	

Option Relate Item			
CH-018	1.8meter HDMI Cable	CU-018	1.8meter USB Cable

KVM 1708WPD M6