

USB HUB DB15 LCD Console Drawers

Optimize rack space. Maximize rack monitoring



↑ (USB Port for device access)

Our range of LCD console drawers provides a variety of features that simplify to access servers to making system monitoring, troubleshooting and software upgrades.

The self-locking rails when in the fully extended open position and the ultra convenient auto lock release when the LCD panel is closed, make for simple and hassle free operation.


Available with 17" or 19" A-Grade LCD panels, combo DB15 8 or 16 port integrated KVM switch & additional one USB local console.

Support USB HUB 2.0 and touch screen enable function.




Features

- Support USB interface, VGA-USB.
- Front 1x USB, Rear 2x USB 2.0 Type A, Sharing USB peripheral Device for computer (ex, flash disk ,hard driver, KB/Mouse).
- Additional one USB Local console to add local KB/Mouse & VGA.
- Durable 104-key keyboard and touch pad.
- Quick and simple installation.
- Self-locking and auto release rails for ultra convenience.
- Port selection via push buttons or On-Screen-Display (OSD).



Rear of KVM-1708P/1908P-M2/ULC



Rear of KVM-1716P/1916P-M2/ULC

Part No.		KVM-1708P-M2/ULC	KVM-1716P-M2/ULC		KVM-1908P-M2/ULC	KVM-1916P-M2/ULC
Direct no. of Computers		8	16		8	16
Maximum no. of Computers		8	16		8	16
LCD	Size	17"		19"		
	Backlight	LED		LED		
	Resolution	1280*1024		1280*1024		
	Max. color	16.7M		16.7M		
	Luminance	250cd/m2		250cd/m2		
	View Angel (H/V)	176 / 170		170 / 160		
	Contrast Ratio	1000 : 1		1000 : 1		
Port Selection	N/A	Push Button, OSD or Hotkey		N/A	Push Button, OSD or Hotkey	
USB Local console	N/A	Yes, USB x2 for KB/ Mouse , VGA x1		N/A	Yes, USB x2 for KB/ Mouse , VGA x1	
USB HUB	Yes, Front 1x USB 2.0 , Rear 2x USB 2.0 Type A for USB Peripheral Device					
Touch Screen	Yes, for option (Driver needed)					
KB/Mouse Emulation	USB					
Rack Depth	500mm to 1100mm (rack cabinet front rails to rear rails)					
Power	100-240V AC 50/60Hz via IEC Type power cord					
Environment	Operation temp: 0 to 50°C Storage temp: -20 to 60°C Humidity: 10% - 90%, non-condensing Shock: 10G acceleration (11ms duration) Vibration: 17 to 500Hz 1G PTP					
Physical Dimensions / Net Weights	448x42x600mm (WxHxD) / 12.5KG			448x42x600mm (WxHxD) / 13.0KG		
Packing Dimensions / Gross weights	720x190x800mm (WxHxD) / 18.5KG			720x190x800mm (WxHxD) / 19.5KG		
Accessory						
1.8meter IEC Type Power Cord (1.8meter VGA Cable Male to Male + 1.8meter USB Cable A Type to A Type for KVM-1701P/1901P-M2)						
Option Relate Item						
CVU-018	1.8meter 2-in-1 KVM Cable-USB&VGA		CVU-030	3.0meter 2-in-1 KVM Cable-USB&VGA		
CVU-050	5.0meter 2-in-1 KVM Cable-USB&VGA					

SAIS - Sacasa Industries & Systèmes

8 rue André Marie Ampère

28500 Vernouillet - France

09 70 440 600 - (+ 33) 970 440 600

<https://clavier-ecran-rackable.fr>

contact@sacasa.info