

Combo CAT6 LCD Console Drawers

Optimize rack space. Maximize rack monitoring



Optional Remote IP Access

- An expansion slot allows you to add an optional KVM over IP module to enable remote access to your servers.
- Gain BIOS level access to your servers for system maintenance, support or failure recovery via secure SSL authentication and encryption.



Our range of LCD console drawers provides a variety of features that simplify to access servers to making system monitoring, troubleshooting and software upgrades.

The self-locking rails when in the fully extended open position and the ultra-convenient auto lock release when the LCD panel is closed, make for simple and hassle free operation.

Available with 17.3" A-Grade LCD panels, Combo CAT6 8, 16 or 32 port integrated KVM switch & a remote IP console.


Using CAT5 or CAT6 ethernet cable, support max. Computer distance up to 40 meters away.

Features


- Support combo interface, VGA-USB & VGA-PS/2.
- Up to 40 meters between Servers to KVM.
- Durable 104-key keyboard and touch pad.
- Quick and simple installation.
- Self-locking and auto release rails for ultra-convenience.
- Port selection via push buttons or On-Screen-Display (OSD).
- Dedicated daisy chain port to expand up to 256 servers.
- Access Control List (ACL) security function for up to 8 independent user accounts.



Rear of KVM-1708W-ASL-M2



Rear of KVM-1716W-ASL-M2



Rear of KVM-1732W-ASL-M2

Part No.	KVM-1708W-ASL-M2	KVM-1716W-ASL-M2	KVM-1732W-ASL-M2
Direct no. of Computers	8	16	32
Maximum no. of Computers	232(Daisy Chain)	240(Daisy chain)	256(Daisy chain)
LCD	Size	17.3"	
	Backlight	LED	
	Resolution	1920*1080 Full HD (support resolution up to 1920x1200)	
	Max. color	262K	
	Luminance	300cd/m2	
	View Angel (H/V)	140 / 120	
Contrast Ratio	3000 : 1		
Port Selection	Push Button, OSD or Hotkey		
Expansion Slot	Yes, option for Remote IP Access		
Max. Computer Distance	40 meters (Servers to KVM)		
KB/Mouse Emulation	USB & PS2		
Rack Depth	500mm to 1100mm (rack cabinet front rails to rear rails)		
Power	100-240V AC 50/60Hz via IEC Type power cord		
Environment	Operation temp: 0 to 50°C Storage temp: -20 to 60°C Humidity: 10% - 90%, non-condensing Shock: 10G acceleration (11ms duration) Vibration: 17 to 500Hz 1G PTP		
Physical Dimensions / Net Weights	448x42x580mm (WxHxD) / 12.0KG	448x42x580mm (WxHxD) / 12.5KG	
Packing Dimensions / Gross weights	715x140x780mm (WxHxD) / 18.0KG	715x140x780mm (WxHxD) / 18.5KG	

Accessory

1.8meter IEC Type Power Cord

Option Relate Item

DGU	CAT6 KVM Dongle-USB&VGA	DGP	CAT6 KVM Dongle -PS/2&VGA
DGD	CAT6 KVM Dongle-USB&DVI	DIP-101	KVM over IP module for Remote Bios Level Access

SAIS - Sacasa Industries & Systèmes

8 rue André Marie Ampère

28500 Vernouillet - France

09 70 440 600 - (+ 33) 970 440 600

<https://clavier-ecran-rackable.fr>

contact@sacasa.info