

Combo CAT6 LCD Console Drawers

Optimize rack space. Maximize rack monitoring



Features

Our range of LCD console drawers provides a variety of features that simplify to access servers to making system monitoring, troubleshooting and software upgrades.

The self-locking rails when in the fully extended open position and the ultra convenient auto lock release when the LCD panel is closed, make for simple and hassle free operation.


Available with 17.3" A-Grade LCD panels, Combo CAT6 8, 16 or 32 port integrated KVM switch & additional one USB local console.

Using CAT5 or CAT6 ethernet cable, support max. Computer distance up to 40 meters away.


- Support combo interface, VGA-USB & VGA-PS/2.
- Additional one USB Local console to add local KB/Mouse & VGA.
- Up to 40 meters between Servers to KVM.
- Durable 104-key keyboard and touch pad.
- Quick and simple installation.
- Self-locking and auto release rails for ultra convenience.
- Port selection via push buttons or On-Screen-Display (OSD).
- Dedicated daisy chain port to expand up to 256 servers.



Rear of KVM-1708W-ASL-M2/ULC



Rear of KVM-1716W-ASL-M2/ULC



Rear of KVM-1732W-ASL-M2/ULC

Part No.	KVM-1708W-ASL-M2/ULC	KVM-1716W-ASL-M2/ULC	KVM-1732W-ASL-M2/ULC
Direct no. of Computers	8	16	32
Maximum no. of Computers	232(Daisy Chain)	240(Daisy chain)	256(Daisy chain)
LCD	Size	17.3"	
	Backlight	LED	
	Resolution	1920*1080 Full HD (support resolution up to 1920x1200)	
	Max. color	262K	
	Luminance	300cd/m2	
	View Angel (H/V)	140 / 120	
Contrast Ratio	3000 : 1		
Port Selection	Push Button, OSD or Hotkey		
USB Local console	Yes , USB x2 for KB/ Mouse , VGA x1		
Max. Computer Distance	40 meters (Servers to KVM)		
KB/Mouse Emulation	USB & PS2		
Rack Depth	500mm to 1100mm (rack cabinet front rails to rear rails)		
Power	100-240V AC 50/60Hz via IEC Type power cord		
Environment	Operation temp: 0 to 50°C Storage temp: -20 to 60°C Humidity: 10% - 90%, non-condensing Shock: 10G acceleration (11ms duration) Vibration: 17 to 500Hz 1G PTP		
Physical Dimensions / Net Weights	448x42x580mm (WxHxD) / 12.0KG		448x42x580mm (WxHxD) / 12.5KG
Packing Dimensions / Gross weights	715x140x780mm (WxHxD) / 18.0KG		715x140x780mm (WxHxD) / 18.5KG

Accessory

1.8meter IEC Type Power Cord

Option Relate Item

DGU	CAT6 KVM Dongle-USB&VGA	DGP	CAT6 KVM Dongle -PS/2&VGA
DGD	CAT6 KVM Dongle-USB&DVI		

SAIS - Sacasa Industries & Systèmes
8 rue André Marie Ampère
28500 Vernouillet - France
09 70 440 600 - (+ 33) 970 440 600
<https://clavier-ecran-rackable.fr>
contact@sacasa.info