

# Dual Rail Combo CAT6 LCD Console Drawers

Optimize rack space. Maximize rack monitoring



CAT6 KVM Dongle-USB&VGA (DGU)



DVI changer



HDMI changer




DP changer

## Features


- Support combo interface, VGA-USB & VGA-PS/2.
- Additional one USB Local console to add local KB/Mouse & VGA.
- Dual slide rail capable LCD screen and keyboard tray independent Operate.
- Up to 40 meters between Servers to KVM.
- Durable 104-key keyboard and touch pad.
- Quick and simple installation.
- Self-locking and auto release rails for ultra-convenience.
- Port selection via push buttons or On-Screen-Display (OSD).



Rear of KVMD-1708/1908ASL-M6/ULC



Rear of KVMD-1716/1916ASL-M6/ULC



Rear of KVMD-1732/1932ASL-M6/ULC

Part No.	KVMD-1708ASL-M6/ULC	KVMD-1716ASL-M6/ULC	KVMD-1732ASL-M6/ULC	KVMD-1908ASL-M6/ULC	KVMD-1916ASL-M6/ULC	KVMD-1932ASL-M6/ULC
Direct no. of Computers	8	16	32	8	16	32
Maximum no. of Computers	232(Daisy Chain)	240(Daisy chain)	256(Daisy chain)	232(Daisy Chain)	240(Daisy chain)	256(Daisy chain)
LCD	Size	17"		19"		
	Backlight	LED		LED		
	Resolution	1280*1024		1280*1024		
	Max.color	16.7M		16.7M		
	Luminance	250cd/m2		250cd/m2		
	View Angel (H/V)	176 / 170		170 / 160		
Contrast Ratio	1000 : 1		1000 : 1			
Port Selection	Push Button, OSD or Hotkey					
USB Local console	Yes, USB x2 for KB/ Mouse, VGA x1					
Max. Computer Distance	40 meters ( Servers to KVM )					
KB/Mouse Emulation	USB & PS2					
Rack Depth	522mm to 1100mm ( rack cabinet front rails to rear rails )					
Power	100-240V AC 50/60Hz via IEC Type power cord					
Environment	Operation temp: 0 to 50°C Storage temp: -20 to 60°C Humidity: 10% - 90%, non-condensing Shock: 10G acceleration ( 11ms duration) Vibration: 17 to 500Hz 1G PTP					
Physical Dimensions / Net Weights	449.8x44.4x685mm (WxHxD) / 13.0KG			449.8x44.4x685mm (WxHxD) / 13.5KG		
Packing Dimensions / Gross weights	710x185x910mm (WxHxD) / 20.0KG			710x185x910mm (WxHxD) / 20.5KG		

### Accessory

1.8meter IEC Type Power Cord

### Option Relate Item

DGU	CAT6 KVM Dongle-USB&VGA	DVI changer	DVI-to-VGA changer
DP changer	DisplayPort-to-VGA changer	HDMI changer	HDMI-to-VGA changer

**SAIS - Sacasa Industries & Systèmes**  
**8 rue André Marie Ampère**  
**28500 Vernouillet - France**  
**09 70 440 600 - (+ 33) 970 440 600**  
<https://clavier-ecran-rackable.fr>  
[contact@sacasa.info](mailto:contact@sacasa.info)