

Dual Rail Combo DB15 LCD Console Drawers

Optimize rack space. Maximize rack monitoring



Our range of LCD console drawers provides a variety of features that simplify to access servers to making system monitoring, troubleshooting and software upgrades.


Flexible dual rail design, capable LCD screen and keyboard tray operated independently.

The self-locking rails when in the fully extended open position and the ultra-convenient auto lock release when the LCD panel is closed, make for simple and hassle free operation.

Available with 17" or 19" A-Grade LCD panels, combo DB15 8 or 16 port integrated KVM switch & additional one USB local console.

Features

- Support combo interface, VGA-USB & VGA-PS/2.
- Additional one USB Local console to add local KB/Mouse & VGA.
- Dual slide rail capable LCD screen and keyboard tray independent Operate.
- Durable 104-key keyboard and touch pad.
- Quick and simple installation.
- Self-locking and auto release rails for ultra-convenience.
- Port selection via push buttons or On-Screen-Display (OSD).
- Dedicated daisy chain port to expand up to 240 servers.



Rear of KVMD-1708/1908AST-M6/ULC



Rear of KVMD-1716/1916AST-M6/ULC

Part No.		KVMD-1708AST-M6/ULC	KVMD-1716AST-M6/ULC	KVMD-1908AST-M6/ULC	KVMD-1916AST-M6/ULC
Direct no. of Computers		8	16	8	16
Maximum no. of Computers		232(Daisy Chain)	240(Daisy chain)	232(Daisy Chain)	240(Daisy chain)
LCD	Size	17"		19"	
	Backlight	LED		LED	
	Resolution	1280*1024		1280*1024	
	Max.color	16.7M		16.7M	
	Luminance	250cd/m2		250cd/m2	
	View Angel (H/V)	176 / 170		170 / 160	
	Contrast Ratio	1000 : 1		1000 : 1	
Port Selection	N/A	Push Button, OSD or Hotkey		N/A	Push Button, OSD or Hotkey
USB Local console	Yes, USB x2 for KB/ Mouse, VGA x1				
KB/Mouse Emulation	USB & PS2				
Rack Depth	522mm to 1100mm (rack cabinet front rails to rear rails)				
Power	100-240V AC 50/60Hz via IEC Type power cord				
Environment	Operation temp: 0 to 50°C Storage temp: -20 to 60°C Humidity: 10% - 90%, non-condensing Shock: 10G acceleration (11ms duration) Vibration: 17 to 500Hz 1G PTP				
Physical Dimensions / Net Weights	449.8x44.4x685mm (WxHxD) / 13.0KG			449.8x44.4x685mm (WxHxD) / 13.5KG	
Packing Dimensions / Gross weights	710x185x910mm (WxHxD) / 20.0KG			710x185x910mm (WxHxD) / 20.5KG	
Accessory					
1.8meter IEC Type Power Cord					
Option Relate Item					
CVU-018	1.8meter 2-in-1 KVM Cable-USB&VGA		CVP-018	1.8meter 3-in-1 KVM Cable-PS/2&VGA	
CVU-030	3.0meter 2-in-1 KVM Cable-USB&VGA		CVP-030	3.0meter 3-in-1 KVM Cable-PS/2&VGA	
CVU-050	5.0meter 2-in-1 KVM Cable-USB&VGA		CVP-050	5.0meter 3-in-1 KVM Cable-PS/2&VGA	

SAIS - Sacasa Industries & Systèmes

8 rue André Marie Ampère


28500 Vernouillet - France

09 70 440 600 - (+ 33) 970 440 600

<https://clavier-ecran-rackable.fr>

contact@sacasa.info

Rear of KVMD-1708/1908AST-M6/ULC



Rear of KVMD-1716/1916AST-M6/ULC

