



DKM 17HD / T

**2U Rack Mount Triple Monitor Console with
– Keyboard Option – Resolution 5760×1080.**



DKM 17HD/T utilized three 17.3" LCD monitors in 2U rack mount drawer with keyboard/touch pad option. The drawer also includes a pair of amplified stereo speakers.

Dual rail design allows monitors and the keyboard pull out and operate on its own. The unit can be fit into any standard rack chassis ranging from 22.3" – 34" deep.

Perfect idea to save valuable rack space for maximal use of the rack.

PRODUCT DESCRIPTION

17.3" HD LCD Monitor

The LCD monitors are built inside a slim and rugged aluminum housing for durability. The display mechanism is hinged so that it can be tilted to the most comfortable viewing position. LCD folds flat on top of keyboard when recessed into the drawer. An auto shut-off switch will turn-off the power to the LCD monitor when the LCD is in recess position.

Keyboard and Pointing Device (DKM-17HD/ TK)

DKM 17HD/TK has optional built in keyboard and touch pad in 2nd drawer below the monitors that operates independently.

Power Supply and Ports

The LCD monitor is powered by a 60W 100-240V full-range power supply positioned at the back of the drawer with a rocker on-off switch. The keyboard, pointing device and video connectors are also positioned at the back of the drawer for easy access.

Security

A key locking mechanism locks the drawer when in the full recess position, to prevent unauthorized access.

SPECIFICATIONS

General Specifications

LCD size: 17.3" x 3

Resolution: 5760x1080

Color: 262K

Brightness: 300 cd/m2

Contrast: 400:1

Response: 8ms

Video Input: Display Port, mini DP,
HDMI, DVI

Interface: USB

Mouse type: Touch pad

Sound: Amplified stereo speakers

Dimension and Weight

Height: 3.5" (2U)

Width: 19"

Depth: 22.3" – 34" ad-
justable

Weight: 39LBS

Operating Environment

Temperature: 0 to 50°C

Humidity: Meth 5%-95% RH, non-
condensing

Altitude: 15,000 ft.

Shock: 15g, 11ms

Vibration: 20-60Hz, 0.075mm

Drop: 3 feet height free drop

EMI & Safety: FCC Class B, CE

Storage Environment

Temperature: -20 to 50°C

Humidity: Meth 5%-95% RH, non-
condensing

Altitude: 40,000 ft.

Shock: 50g, 11ms

Vibration: 10-50Hz, 0.15mm

Drop: 3 feet height free drop

EMI & Safety: FCC Class B, CE



