

Panel Mount Industrial Display Monitor

Model # IPMB-15W




Features

- 6mm aluminum front bezel with hardness glass protect screen
- 15.6 inch wide screen , support 1920x1080 resolution
- DVI-D, VGA, Audio input
- Front bezel NEMA4 / IP65 compliant
- Front osd control buttons to optimized display
- Build in 2x 2watts stereo speakers
- Panel (Flush) mount with clips
- Meet standard VESA hole, support desk stand / wall mount / Swing Arm mounting

Option

- Composite video input
- BNC Loop-in-out
- HDMI or Display port input
- 3G / HD / SD-SDI broadcast grade input
- DC 9~36 V power input
- AR Hardness glass
- Touch screen



LCD Characteristics :

Screen Size	15.6"
Backlight Type	LED
Resolution	1920 x 1080
Contrast Ratio	400:1
Brightness (cd/m2)	220
View Angles (H/V)	120/100
Max. Color	262K
MTBF (Hrs.)	12,000

Power Specifications :

AC Power Input	External Power Adapter , 100-240V AC Input
Wide Range DC Power Input (option)	Screw Type Terminal Block with internal wide Range DC 9-36V power module

Input Signals:

DVI-D	DVI-D 24Pin Connector (Female)
VGA	D-SUB 15Pin Connector (Female)
Audio	3.5" Jack
Power Input	12V DC jack with hanger
Touch-USB (option)	USB A Type connector
Touch-RS232 (option)	D-SUB 9P connector (Female)

Mechanical and Environment:

IP Protect	Front IP65 Grade
Mounting	Panel (Flush) Mount with clips, VESA Mount
Construction	Aluminum Front Bezel + Metal Housing
Operating Temperature	0 - 50 deg. C
Operating Humidity	5% - 95% (non -condensing)
Anti-Vibration	5 - 500 Hz / 1 Grms PTP
Anti-Shock	15G / Peak (11 ms)
Physical Dimension (WxHxD)	400 x 275 x 54 (mm)
Packing Dimension (WxHxD)	505 x 380 x 200 (mm)
Net Weight / Gross Weight	5.5 / 7(KGs)
Certification and Approvals	CE / FCC / RoHS

User Controls Interface:

Power ON / OFF via Front Button
Power Mode Status LED indicator
OSD (On Screen Display) Buttons

